# POINT-OF-SALE PRINTER
## TM-T82X

**EPSON**
EXCEED YOUR VISION

# FLEXIBILITY
## AND RELIABILITY
### AT YOUR
## FINGERTIPS.

*Compact and Durable*

Enjoy the power of reliability and flexibility in your business with the cost effective TM-T82X. Printing at a high speed of 200mm/s, the easy-to-configure printer supports USB, Ethernet, and RS-232, and can be fitted anywhere thanks to its compact and durable body. A perfect companion for small business owners.

| Compact | Print | Auto Cutter | Cost Effective | Built-in Power Supply |
|---|---|---|---|---|

## IT'S IN THE DETAILS.

**Unrivalled Performance**
With a MCBF of 60 million lines and an auto-cutter life of 1.5 million cuts.

**Ease-of-use**
Features drop-in paper loading, auto-cutter and status LEDs.

**Adaptive Design**
Space saving compact design makes it easy to suit event the most demanding retail environment.

# SPECIFICATIONS
## TM-T82X

**EPSON**
EXCEED YOUR VISION

| MODEL NUMBER | | TM-T82X |
|---|---|---|
| **Printing Method** | | Thermal line printing |
| **Print Font** | | |
| Font | | 9 × 17 / 12 × 24, Hanji Font: 24 x 24, Thai Font: 9 x 24 / 12 x 24 |
| Character Size (W x H) | | 0.88 × 2.13 mm / 1.25 × 3 mm, Hanji font: 3 x 3 mm, Thai font: 0.88 x 3 mm / 1.25 x 3 mm |
| Character Set | | 95 Alphanumeric, 18 set International, 128 × 43 pages (including Thai / Viet and user-defined page) |
| | | Hanzi: Simplified Chinese: GB18030-2000: 28,553 |
| | | Bar code: UPC-A, UPC-E, JAN13(EAN13), JAN8(EAN), CODE39, ITF, CODABAR(NW-7), CODE93, CODE128, GS1-128, GS1 DataBar |
| | | Two-dimensional code: PDF417, QRCode, MaxiCode, 2D GS1 DataBar, Composite Symbology |
| Characters Per Inch | | 22.6cpi / 16.9cpi, Hanji Font: 7.8cpi, Thai Font: 22.6cpi / 16.9cpi |
| **Interface** | | Built-in USB + Serial (9pin) / Ethernet Interface |
| **Receive Data Buffer** | | 4KB or 45 bytes |
| **Print Speed** | | Max 200mm/s |
| **Dot Density** | | 203 x 203 dpi |
| **Paper** | | |
| Roll Paper | Width and Roll Diameter | 79.5 ± 0.5 mm |
| **Power** | | |
| Supply Voltage | | AC 100 to 230V / 50 to 60 Hz |
| Power Consumption | | |
| Operating | | Approx. 27.8 W |
| Standby | | Approx 0.96 W |
| Power Supply | | Built-in power supply |
| **Reliability** | | |
| Printer Mechanism Life | | 15 million lines |
| Auto Cutter Life | | 1.5 million cuts |
| MTBF | | 360,000 hours |
| MCBF | | 60,000,000 lines |
| **Overall Dimensions (D x W x H)** | | 192 x 149 x 140 mm |
| **Mass** | | Approx. 1.5 kg |
| **EMI and Safety Standards** | | Singapore IEC62368-1 |
| **Option** | | External buzzer unit |
| **Standard Accessories ROM** | | Roll paper × 1 roll (for checking the initial movement of the printer), |
| | | Setup guide, USB cable for USB + Serial model |
| **Installation** | | Horizontally |
| **Driver Supported OS** | | Windows, Mac, Linux |
| **Driver Features** | | True Font Replacement |
| **Built-in Feature** | | Automatic Paper Reduction, Automatic paper cut with logo printing, |
| | | QRCode Quick Pairing (for Ethernet Model only) |

### Dimensions & Weight

**Weight:** Approx. 1.5 kg



140mm (5.52")
192mm (7.56")
149mm (5.87")

### Legend

| dpi | dots per 25.4 mm (dots per inch) |
|---|---|
| cpi | characters per 25.4 mm (characters per inch) |

Dealer's Stamp

**Sales Enquiries**
**800 120 5564**

 EpsonSEA   @EpsonSEA   @EpsonSEA   EpsonSoutheastAsia   Epson Southeast Asia

For latest specifications, visit **www.epson.com.sg** or call **+65 800 120 5564.**